

Wave 130RK

Eco-friendly compact high brightness 4K UHD laser projector









- Incredible True 4K UHD resolution and laser technology - HDR and HLG compatible
- Lights on viewing bright 4000 lumens Perfect for big screen home entertainment and immersive gaming
- Small form factor for easy installation 1.6x zoom, 360-degree and portrait projection
- Lightning-fast gaming Supports 1080p 240Hz at 4.2ms and 4K 60Hz at 17ms



The Wave 130RK is one of Optoma's most compact and hassle-free 4K UHD DuraCore laser projectors to date. Designed for maintenance-free continuous operation, it delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

An added benefit, the Wave 130RK features an external power supply offering more reliability, portability and energy efficiency.

Specifications

Specifications	
Display/image	
Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	4,000 lumens
Contrast ratio	2,300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction -	+/-30°
horizontal	+/-00
Keystone correction - vertical	+/-30°
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 140Khz
Vertical scan rate	24 ~ 240Hz
Uniformity	80%
Screen size	
	0.66m ~ 7.7m (26" ~ 303") diagonal
Lamp info	The second secon
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.4:1 ~ 2.24:1
Projection distance	1.3m - 9.4m
Zoom	1.6
Zoom type	Manual
Focal length	20.91 ~ 32.62
Native offset	116%
Connectivity	
Connections	Inputs 1 x HDMI 2.0, 1 x HDMI 2.0 (eARC)
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x RJ45, 1 x RS232
General	
Noise level (min)	28dB
Noise level (max)	35dB
	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Noise level (max)	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
Noise level (max) PC compatibility	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
Noise level (max) PC compatibility 2D compatibility	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Noise level (max) PC compatibility 2D compatibility 3D compatibility	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H//MVN, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IRCA 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian,
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H//MVN, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian,
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IRCA 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian,
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MJ, 3.58MHz, 4.43MHz PAL BrD/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H//MVN, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W AC power cord
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H//MVN, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker In the box	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Nonwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W AC power cord Remote control
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker In the box	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W AC power cord Remote control Basic user manual
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker In the box Input lag Power	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H//MVN, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W AC power cord Remote control Basic user manual 4.20ms
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker In the box Input lag Power Power supply	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 9°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W AC power cord Remote control Basic user manual 4.20ms External power supply, 100V ~ 240V, 50-60Hz
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker In the box Input lag Power Power supply Power consumption (standby)	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W AC power cord Remote control Basic user manual 4.20ms External power supply, 100V ~ 240V, 50-60Hz <0.5W
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker In the box Input lag Power Power supply Power consumption (standby) Power consumption (min)	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W AC power cord Remote control Basic user manual 4.20ms External power supply, 100V ~ 240V, 50-60Hz <0.5W 146.05W
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker In the box Input lag Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W AC power cord Remote control Basic user manual 4.20ms External power supply, 100V ~ 240V, 50-60Hz <0.5W
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker In the box Input lag Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W AC power cord Remote control Basic user manual 4.20ms External power supply, 100V ~ 240V, 50-60Hz <0.5W 146.05W 215.05W
Noise level (max) PC compatibility 2D compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker In the box Input lag Power Power ronsumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H)	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MJ, 3.58MHz, 4.43MHz PAL BrD/G/H//M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W AC power cord Remote control Basic user manual 4.20ms External power supply, 100V ~ 240V, 50-60Hz <0.5W 146.05W 274 x 216 x 114
Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Speaker count Watts per speaker In the box Input lag Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	35dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) Full 3D Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft 1 15W AC power cord Remote control Basic user manual 4.20ms External power supply, 100V ~ 240V, 50-60Hz <0.5W 146.05W 215.05W

